

(43) Date of A Publication 29.10.1997

GB 2312 561 A

FIG. 1





FIG. 2



antenna apparatus will be described.

A length of the antenna element 101 is a quarter of a wavelength used and acts as a monopole antenna. A length of the balun 107 is adjusted to a quarter of a wavelength
5 to provide a tuned condition at the used frequency. An impedance of the outer conductor 103 viewed from the connection point 106 becomes an infinite at an opposite end from the connection point 106, that is, that point shows an open condition, so that if a voltage is applied to that
10 point, no current flows through the outer conductor 103. As the result, this prevents an unbalanced current from flowing through an earth of the radio wave circuit from the antenna side and prevents a deterioration of a characteristic of the radio wave circuit 105.

15

The aim of the present invention is to provide an improved antenna apparatus.

According to the present invention, an antenna apparatus is provided, which comprises: an antenna element
20 having a first electrical length and a feeding point at an end thereof; and a coaxial cable having an inner conductor and a coaxial outer conductor having a second electrical length, one end of the inner conductor being connected to the feeding point, another end of the inner conductor and a
25 corresponding end of the coaxial outer conductor being to

be coupled to a radio wave circuit, the first and second electrical lengths being determined to have a resonance to transmit a radio wave signal from the antenna element and the outer conductor on a transmission mode.

In the antenna apparatus, the first and second electrical lengths may be substantially a quarter of a wave length used.

In the antenna apparatus, the coaxial cable may be flexible.

The features of the present invention will become more apparent from the following detailed description of an exemplary embodiment and the accompanying drawings, in which:-

Fig. 1 is a cross-sectional side view of an antenna apparatus of an embodiment of the present invention;

Fig. 2 is an illustration of this embodiment showing current amplitudes along the antenna element and the outer conductor of the antenna apparatus; and

Fig. 3 is a cross-sectional side view of a prior art sleeve antenna.

The same or corresponding elements or parts are designated with like references throughout the drawings.

Hereinbelow will be described an embodiment of this

invention.

Fig. 1 is a cross-sectional side view of an antenna apparatus of the embodiment of the present invention. In Fig. 1, numeral 1 denotes an antenna element having a helical form electrically connected to an inner conductor 3 of the coaxial cable 8 at a feeding point 2. An outer conductor 4 is provided around the inner conductor 3 of the coaxial cable. That is, the inner conductor 3, the outer conductor 4, an insulator between the inner conductor 3 and the outer conductor 4 form the coaxial cable 8. The inner conductor 3 and the outer conductor 4 are connected to a radio wave circuit 6 at the connection points 5 and transmits an electric power from the radio wave circuit portion 6 to the feeding point 2. Numeral 7 denotes a case of the radio wave apparatus including this antenna apparatus and the radio wave circuit 6.

An operation of the antenna apparatus having the structure as mentioned above will be described.

Fig. 2 is an illustration of this embodiment showing current amplitudes along the antenna element 1 and the outer conductor 4. The antenna element 1 has an electrical length EL of a quarter of a wavelength λ of the used frequency and energized by a current flowing thereinto through the feeding point 2. A current flowing through the outer conductor 4 is induced by the current flowing through

the inner conductor 3 and is reflected at an end of the outer conductor 4 corresponding to the feeding point 2 and then, flows toward the connection point 5. Assuming that a length L of the coaxial cable 8 is a quarter of a
5 wavelength of the used frequency, since the current at the feeding point 2 is maximum, a current flowing through the outer conductor 4 of the coaxial cable 8 at the connecting point 5 is zero. Accordingly, a standing wave is generated along the antenna element 1 and the outer conductor 4 of
10 the coaxial cable 8. That is, a current distribution is provided which shows a maximum current amplitude at the feeding point 2 and a minimum amplitude, that is, zero, at the connection point 5 on the opposite side from the tip portion of the antenna element 1, so that a resonance
15 condition is provided. Thus, a dipole antenna is formed by the antenna element 1 and the outer conductor 4 of the coaxial cable, wherein the outer conductor 4 of the coaxial cable acts as an emission element. In this condition, the current in the outer conductor 4 of the coaxial cable 8 at
20 the connecting point 5 is zero, so that the outer conductor 4 is electrically disconnected from the radio wave circuit 6. Accordingly, an unnecessary current flows into an earth of the radio wave circuit 6 from the antenna side. As the
25 result, the earth of the radio wave circuit 6 does not act as an antenna, so that a characteristic of the radio wave

circuit 6 is not disturbed.

As mentioned, because, according to the embodiment mentioned above, the resonance condition is provided by generating the standing wave along the antenna element 1 and the outer conductor 4 of the coaxial cable 8 by setting the length L of the coaxial cable to the quarter of the wavelength of the used frequency. The outer conductor 4 of the coaxial cable 8 can act as the emission element, so that an unbalanced current can be prevented from flowing into the radio wave circuit 6. Moreover, because the coaxial cable has an elasticity, the antenna element 1 and the radio wave circuit portion 6 are made close each other, so that the antenna apparatus can be miniaturized.

In the above-mentioned embodiment, the length L of the coaxial cable 8 is assumed as the quarter of the wavelength. The length of the coaxial cable is affected by parts or the like arranged around the coaxial cable, so that the length may vary with the its circumference condition.

As mentioned the antenna apparatus of this embodiment comprises the antenna element 1 having the electrical length EL and the feeding point 2 at an end thereof; and the coaxial cable 8 having the inner conductor 3 and the coaxial outer conductor 4 respectively having an electrical length L, one end of the inner conductor 3 being

connected to the feeding point 2, another end of the inner conductor 3 and a corresponding end of the coaxial outer conductor being to be coupled to the radio wave circuit 6 at the connection points 5, the electrical lengths EL and L 5 being determined to have a resonance to transmit a radio wave signal from the antenna element 1 and the outer conductor 4 on a transmission mode.

The electrical lengths EL and L are substantially a quarter of a wave length used. Moreover, the coaxial cable 8 may be flexible.

C L A I M S

1. An antenna apparatus comprising:
an antenna element having a first electrical length
5 and a feeding point at an end thereof; and
a coaxial cable having an inner conductor and a
coaxial outer conductor respectively having a second
electrical length, one end of said inner conductor being
connected to said feeding point, another end of said inner
10 conductor and a corresponding end of said coaxial outer
conductor being to be coupled to a radio wave circuit, said
first and second electrical lengths being determined to
have a resonance to transmit a radio wave signal from said
antenna element and said outer conductor on a transmission
15 mode.
2. An antenna apparatus as claimed in claim 1, wherein
said first and second electrical lengths are substantially
a quarter of a wave length used.
3. An antenna apparatus as claimed in claim 1 or 2,
wherein said coaxial cable is flexible.
4. A radio frequency apparatus comprising: a radio
frequency circuit; and an antenna, said antenna comprising:
an antenna element having a first electrical length and
a feeding point at one end; and

a coaxial cable having a second electrical length and including an inner conductor and a coaxial outer conductor, a first end of said inner conductor being connected to said feeding point and a second end of said conductor being directly connected to said radio frequency circuit, wherein said first and second electrical lengths are determined so as that said antenna is substantially resonant at a radio frequency to be transmitted from said radio frequency circuit.

5. A radio frequency apparatus according to claim 4 having no balun associated with said antenna.

6. An antenna apparatus constructed and arranged to operate substantially as hereinbefore described with reference to and as illustrated in Figures 1 and 2 of the accompanying drawings.



Harada Industries (Europe) Ltd
% Mathys & Squire
100 Grays Inn Road
LONDON
WC1X 8AL

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

Examiner: 01633 813710
†E-mail: andrew.glanfield@patent.gov.uk
Switchboard: 01633 814000
Fax: 01633 814444

Your Reference: MCM\21303
Application No: GB 9913526.1

27 September 1999

Dear Sirs

Patents Act 1977: Search Report under Section 17(5)

I enclose two copies of my search report and a copy of the citations.

Scope of search

Due to the broad nature of claims 1 and 18, especially in the light of the last paragraph of page 1 of your application, I have restricted my search to the subject matter of the narrower claim 1 where the antenna is formed as a **planar** spiral as in your specific embodiments.

MATSUSHITA and GEC MARCONI are cited below as examples of helical antennae which fall within claim 1. The additional five citations show planar spiral antennae according to your invention.

A further search may be necessary once you have made suitable amendments to your claims to more precisely define your invention. When making such amendments you should ensure that all your independent claims are linked by a single inventive concept.

Publication

I estimate that, provided you have met all formal requirements, preparations for publication of your application will be completed soon after **7 November 2000**. You will then receive a letter informing you of completion and telling you the publication number and date of publication.

†Use of E-mail: Please note that under patent law e-mail may be used to file correspondence only.



Application No: GB 9913526.1
Claims searched: 1-17

Examiner: Dr Andrew Glanfield
Date of search: 7 October 1999

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.Q): H1Q (QDJ, QDX)
Int Cl (Ed.6): H01Q (1/36, 1/38, 9/27, 11/00, 11/12, 11/14, 11/16, 11/18)
Other: ONLINE: EPODOC, JAPIO, WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage		Relevant to claims
X	GB 2312561 A	(MATSUSHITA) see especially figure 1	1, 3, 9-11, 13, 18
X	GB 2256750 A	(GEC MARCONI) see especially figure 1.	1-3, 9-11, 18
X	GB 1390514	(MARCONI) see especially figures 3 (a) and (b).	1, 3-6, 9-11, 13, 15, 18
X	GB 781672	(STANDARD TELEPHONES) see especially figure 2.	1, 3, 9-11, 13, 15, 18
X	EP 0825674 A1	(NIPPON) see especially figures 1a and 1b and line 3 to line 21 of column 3.	1, 3, 9-11, 13, 18
X	EP 0884796 A2	(MATSUSHITA) see especially figure 2 (b) and figures 3(a) and 3(b).	1, 2, 4-6, 9-11, 13-14, 18
X	US 4511843	(THORAVALL) see figure 14.	1, 4, 5-6, 9-11, 13, 15, 18

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.



Application No: GB 9707420.7
Claims searched: 1 to 5

Examiner: Peter Easterfield
Date of search: 10 June 1997

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.O): H1Q (QDJ, QDK, QDP, QDX, QHC, QHH, QHX, QJA)

Int Cl (Ed.6): H01Q 1/24, 1/27, 9/04, 9/06, 9/14, 9/38

Other: Online: WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB 2141878 A (NRDC) see fig. 4	1-5
A	GB 0526121 A (DE MONGE)	

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.
& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.
E Patent document published on or after, but with priority date earlier than, the filing date of this application.



Application No: GB 9913526.1

Page 2

27 September 1999

Amendment/withdrawal

If you wish to file amended claims for inclusion with the published application, or to withdraw the application to prevent publication, you must do so before the preparations for publication are completed. **No reminder will be issued.** If you write to the Office less than 3 weeks before the above completion date, please mark your letter prominently: "**URGENT - PUBLICATION IMMINENT**".

Yours faithfully

A. R. Glanfield

Dr Andrew Glanfield
Examiner